

U-CROWN

STANDARDNO UKLJUČENO

- WiFi sučelje
- 4 noćne krivulje
- 2-stupanjski kompresor
- I-Feel funkcija
- Inteligentno predzagrijavanje
- Ionizator zraka
- Super tihi rad
- 7 brzina ventilatora
- Zazor od samo 0,8mm



MODEL	UČINAK (W)		SEER / SCOP ENER. KLASA	DIMENZIJE V / Š / D (mm)
	HLADENJE	GRIJANJE		
GWH09UB-K3DNA4F/I	2600 (390-4000)	3000 (560-4800)	7,5/4,6 (A++/A++)	305/860/170 596/899/378
GWH12UB-K3DNA4F/I	3500 (390-4450)	3600 (560-5400)	7,0/4,6 (A++/A++)	305/860/170 596/899/378
GWH18UC-K3DNA4F/I	5275 (900-5750)	5275 (750-7250)	6,1/4,0 (A++/A++)	320/960/205 700/950/396



-30°C ~ 24°C
-18°C ~ 54°C



R410A

CJEVOVOD	UČINAK (kW)		
	2,6	3,5	5,2
Max. visinska razlika [m]	10	10	10
Max. duljina instalacije [m]	15	20	25
Promjer cijevi tekuće faze [mm]	6,35	6,35	6,35
Promjer cijevi plinovite faze [mm]	12,7	12,7	12,7

MODEL	UČINAK (W)		SEER / SCOP ENER. KLASA	DIMENZIJE V / Š / D (mm)
	HLADENJE	GRIJANJE		
GWH09TB-S3DNA2D/I	2600 (600-3200)	3000 (600-4000)	8,5/5,1 (A+++/A+++)	292/866/209 596/899/378
GWH12TB-S3DNA2D/I	3500 (600-4000)	4000 (600-5000)	8,0/4,7 (A++/A++)	292/866/209 596/899/378
GWH18TC-S3DNA2D/I	5300 (1000-6300)	5400 (1000-6800)	6,4/4,0 (A++/A+)	319/1018/230 700/955/396
GWH24TD-S3DNA2F/I	7000 (2000-8600)	7300 (1900-9000)	6,3/4,0 (A++/A+)	326/1178/264 790/980/427

CJEVOVOD	UČINAK (kW)			
	2,6	3,5	5,3	7,0
Max. visinska razlika [m]	10	10	10	10
Max. duljina instalacije [m]	15	20	25	25
Promjer cijevi tekuće faze [mm]	6,35	6,35	6,35	6,35
Promjer cijevi plinovite faze [mm]	9,52	12,7	15,88	15,88



9k i 12k: **-20°C ~ 24°C**
-15°C ~ 48°C

18k i 24k: **-20°C ~ 24°C**
-15°C ~ 43°C

R410A

HANSOL

STANDARDNO UKLJUČENO

- 7 brzina ventilatora
- Duži domet ispuha
- Samodijagnoza
- G10 tehnologija (18k i 24k)
- I-Feel funkcija
- Ionizator zraka
- Healthy filter
- Elektrostatički filter za uklanjanje prašine

