

STANDARDNO UKLJUČENO

- Poboljšana učinkovitost
- Tihi rad s niskom razinom buke
- Econo Cool funkcija
- Tjedni tajmer
- Samodijagnoza
- Automatsko prebacivanje načina rada



MODEL	UČINAK (W)		ENER. KLASA SEER / SCOP	DIMENZIJE V / Š / D (mm)
	HLADENJE	GRIJANJE		
MSZ-HR25VF MUZ-HR25VF	2500 (500-2900)	3150 (700-3500)	6,2 / 4,3 (A++ / A+)	280 / 838 / 228 538 / 699 / 249
MSZ-HR35VF MUZ-HR35VF	3400 (900-3400)	3600 (900-3700)	6,2 / 4,3 (A++ / A+)	280 / 838 / 228 538 / 699 / 249
MSZ-HR42VF MUZ-HR42VF	4200 (1100-4600)	4700 (900-5400)	6,5 / 4,3 (A++ / A+)	280 / 838 / 228 550 / 800 / 285
MSZ-HR50VF MUZ-HR50VF	5000 (1300-5000)	5400 (1400-6500)	6,5 / 4,3 (A++ / A+)	280 / 838 / 228 550 / 800 / 285



 Mogućnost spajanja
na WiFi sučelje

 -10°C ~ 46°C
-10°C ~ 24°C

CJEVOVOD	SNAGA (kW)			
	2,5	3,4	4,2	5,0
Max. visinska razlika [m]	12	12	12	12
Max. dužina instalacije [m]	20	20	20	20
Promjer cijevi tekuće faze [mm]	6,35	6,35	6,35	6,35
Promjer cijevi plinovite faze [mm]	9,52	9,52	9,52	9,52

MODEL	UČINAK (W)		ENER. KLASA SEER / SCOP	DIMENZIJE V / Š / D (mm)
	HLADENJE	GRIJANJE		
MSZ-DM25VA MUZ-DM25VA	2500 (1300-3000)	3150 (900-3500)	5,8 / 4,1 (A+ / A+)	290 / 799 / 232 538 / 699 / 249
MSZ-DM35VA MUZ-DM35VA	3150 (1400-3500)	3600 (1100-4100)	5,7 / 4,1 (A+ / A+)	290 / 799 / 232 538 / 699 / 249

CJEVOVOD	SNAGA [KW]	
	2,5	3,15
Max. visinska razlika [m]	12	12
Max. dužina instalacije [m]	20	20
Promjer cijevi tekuće faze [mm]	6,35	6,35
Promjer cijevi plinovite faze [mm]	9,52	9,52


 Mogućnost spajanja
na WiFi sučelje

 -10°C ~ 24°C
-10°C ~ 46°C

STANDARDNO UKLJUČENO

- Automatsko zakretanje lopatica
- Samodijagnoza
- Funkcija "Econo - Cool"
- 24 satni tajmer
- Auto restart
- Hlađenje pri niskim temperaturama
- Silver-ion filter

