

ZIDNA IZVEDBA

POWER DC INVERTER SERIJA SA R32 RADNIM MEDIJEM

STANDARDNO UKLJUČENO

- 3D I-See senzor
- Area funkcija
- Prepoznavanje korisnika
- Econo-cool funkcija
- Automatska dvostruka krilca
- Tjedni tajmer
- Samodijagnoza
- Replace Tehnologija
- Automatsko prebacivanje načina rada
- Dvostruki premaz
- I-Save način rada
- Plasma Quad plus funkcija
- Noćni način rada

CRVENI
SREBRNI

CRNI
BIJELI


MODEL	UČINAK (W)		ENER. KLASA SEER/SCOP	DIMENZIJE V/S/D (mm)
	HLAĐENJE	GRIJANJE		
CRVENI MODELI				
MSZ-LN25VGR	2500	3200	10,5 / 5,2	307 / 890 / 233
MUZ-LN25VG	(1000-3500)	(800-5400)	(A+++ / A+++)	550 / 800 / 285
MSZ-LN35VGR	3500	4000	9,5 / 5,1	307 / 890 / 233
MUZ-LN35VG	(800-4000)	(1000-6300)	(A+++ / A+++)	550 / 800 / 285
MSZ-LN50VGR	5000	6000	8,5 / 4,6	307 / 890 / 233
MUZ-LN50VG	(1000-6000)	(1000-8200)	(A+++ / A+++)	714 / 800 / 285
MSZ-LN60VGR	6100	6800	7,5 / 4,6	307 / 890 / 233
MUZ-LN60VG	(1400-6900)	(1800-9300)	(A++ / A++)	880 / 840 / 330
SREBRNI MODELI				
MSZ-LN25VGV	2500	3200	10,5 / 5,2	307 / 890 / 233
MUZ-LN25VG	(1000-3500)	(800-5400)	(A+++ / A+++)	550 / 800 / 285
MSZ-LN35VGV	3500	4000	9,5 / 5,1	307 / 890 / 233
MUZ-LN35VG	(800-4000)	(1000-6300)	(A+++ / A+++)	550 / 800 / 285
MSZ-LN50VGV	5000	6000	8,5 / 4,6	307 / 890 / 233
MUZ-LN50VG	(1000-6000)	(1000-8200)	(A+++ / A+++)	714 / 800 / 285
MSZ-LN60VGV	6100	6800	7,5 / 4,6	307 / 890 / 233
MUZ-LN60VG	(1400-6900)	(1800-9300)	(A++ / A++)	880 / 840 / 330
CRNI MODELI				
MSZ-LN25VGB	2500	3200	10,5 / 5,2	307 / 890 / 233
MUZ-LN25VG	(1000-3500)	(800-5400)	(A+++ / A+++)	550 / 800 / 285
MSZ-LN35VGB	3500	4000	9,5 / 5,1	307 / 890 / 233
MUZ-LN35VG	(800-4000)	(1000-6300)	(A+++ / A+++)	550 / 800 / 285
MSZ-LN50VGB	5000	6000	8,5 / 4,6	307 / 890 / 233
MUZ-LN50VG	(1000-6000)	(1000-8200)	(A+++ / A+++)	714 / 800 / 285
MSZ-LN60VGB	6100	6800	7,5 / 4,6	307 / 890 / 233
MUZ-LN60VG	(1400-6900)	(1800-9300)	(A++ / A++)	880 / 840 / 330
BIJELI MODELI				
MSZ-LN25VGW	2500	3200	10,5 / 5,2	307 / 890 / 233
MUZ-LN25VG	(1000-3500)	(800-5400)	(A+++ / A+++)	550 / 800 / 285
MSZ-LN35VGW	3500	4000	9,5 / 5,1	307 / 890 / 233
MUZ-LN35VG	(800-4000)	(1000-6300)	(A+++ / A+++)	550 / 800 / 285
MSZ-LN50VGW	5000	6000	8,5 / 4,6	307 / 890 / 233
MUZ-LN50VG	(1000-6000)	(1000-8200)	(A+++ / A+++)	714 / 800 / 285
MSZ-LN60VGW	6100	6800	7,5 / 4,6	307 / 890 / 233
MUZ-LN60VG	(1400-6900)	(1800-9300)	(A++ / A++)	880 / 840 / 330

R32

 Ukjučeno
WiFi sučelje

 -15°C ~ 24°C
-10°C ~ 46°C

CJEVOVOD	SNAGA (kW)			
	2,5	3,5	5,0	6,1
Max. visinska razlika [m]	12	12	12	15
Max. dužina instalacije [m]	20	20	20	30
Promjer cijevi tekuće faze [mm]	6,35	6,35	6,35	6,35
Promjer cijevi plinovite faze [mm]	9,52	9,52	9,52	12,7